

CLEAN COPY OF CLAIMS AS AMENDED FOR ENTRY

1. A device for scaring birds comprising:
- (a) a silhouette of a bird of prey having at least two holes therethrough;
 - (b) a first line having one end rotatably attached to said hole;
 - (c) a second line having one end rotatably attached to said hole;
 - (d) a third line having:
 - (i) one end rotatably attached to said one end of said first line for rotation of said third line relative said first line; and
 - (ii) another end rotatably attached to said one end of said second line, for rotation of said third line relative said second line

so as to maintain continuity between said one end of said first and second lines respectively when said first and second lines become unattached from said holes respectively.

13. A device for scaring birds comprising:
- (a) a thin vinyl sheet profiling a bird of prey, said sheet including first and second holes there through;
 - (b) first and second grommets for reinforcing said first and second holes;
 - (c) a first swivel connected to said first grommet, said first swivel including first hole attaching means, and first rotatable means;
 - (d) a second swivel connected to said second grommet, said second swivel including second hole attaching means, and second rotatable means;

BEST AVAILABLE COPY

- 2 -

- (e) a first line having an end connected to said first rotatable means for rotatable movement about said first hole attaching means;
 - (f) a second line having an end connected to said second rotatable means for rotatable movement about said second hole attaching means;
 - (g) a safety line having one end connected to said first hole attaching means and another end connected to said second hole attaching means.
18. A method of scaring birds comprising the steps of:
- (a) securing the silhouette of a bird of prey in position by:
 - (i) connecting a first swivel having a first clip and first rotatable means by connecting said first clip to said first hole;
 - (ii) connecting a first end of said first line to said first rotatable means;
 - (iii) connecting a second swivel having a second clip and second rotatable means by connecting said second clip to said first hole,
 - (iv) connecting a first end of said second line to said second rotatable means;
 - (b) reinforcing said silhouette from breakage by connecting one end of a safety line across said silhouette to said first clip and another end of said safety line to said second clip;
 - (c) moving said silhouette by wind so as to scare said birds.
21. A method as claimed in claim 18 including the step of maintaining the continuity between said first end of said first line and said first end of said second line when said first and second clips become disconnected from said holes.

BEST AVAILABLE COPY